



IRA T12 Ultra

Rugged Tablet

- 8.7" narrow-bezel HD display
- Helio G99 chip + Android 14 OS
- Powerful 8000mAh battery, super fast charging
- 48MP rear camera + 32MP front camera
- WIFI 5/4G/BT5.1 multiple communications
- IP68 high protection level, 4 feet drop resistant



IRA T12 Ultra SPECIFICATIONS

- Durability**
- MIL-STD-810H certified
 - 4ft drop 26 faces
 - IP68 certified
 - ±8kV contact discharge, ±12kV air discharge

- Operating System**
- Android 14

- Processor**
- MT8781
 - (6x 2.2Ghz Cortex-A76, 2x 2.0Ghz Cortex-A55)

- Graphics**
- ARM G57 MC2

- Memory**
- 8GB LPDDR4x on board

- Storage**
- 128GB UFS2.2
 - Optional 256GB UFS2.2

- Display**
- 8.7" FHD(800*1340), 400nits · 10-point capacitive touchscreen, support Glove&Water

- Audio**
- Integrated microphone
 - Integrated 2W speaker x2
 - Smart PA

- Camera**
- Integrated 32.0 MP front camera
 - Integrated 48.0 MP rear camera

- Keyboard & Input**
- 3 buttons

- Network & Connectivity**
- Intel® Wi-Fi 5 (802.11 ac)
 - Bluetooth® V5.1
 - Integrated 4G LTE multi-carrier mobile broadband
LTE-FDD(B1/2/3/4/5/7/8/12/17/18/19/20//25/26/28A/28B/66)
LTE-TDD(B34/38/39/40/41)
WCDMA(B1/2/4/5/8)
GSM(B2/3/5/8)
 - Integrated GPS,Beidou,Galileo,Glonass module

- Security**
- Integrated HF-RFID (NFC) reader

- Data Capture**
- Support face unlocking

- I/O Interface**
- USB2.0 (typeC) x1
 - 2 of 3 card slot
(Nano Sim+Micro SD or Nano Sim+Nano Sim)

- Battery & Charging**
- Battery Li-Ion, 3.85V, 8000mAh, 11.2 hours
 - Type-C Adapter

- Environment**
- Operating temperature: -20°C ~ 60°C (-4°F ~ 140°F)
 - Storage temperature: -30°C ~ 70°C (-22°F~158°F)
 - Humidity: 95% (Non-Condensing)

- Dimension**
- 220.14 mm(L) × 135.5 mm(W) × 14 mm(H)

- Weight**
- 569g

- Accessories**
- Standard: Adapter, Cable(typeC), Hand Strap
 - Optional: Film

- Warranty**
- One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 350 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

WISHTEL PVT. LTD.

Visit: www.wishtel.com | Email: info@wishtel.com



A product by
WISHTEL
AN INDIAN BRAND

